West Bengal State Warehousing Corporation

(A Government Undertaking) KHADYASHREE BHAVAN (1ST. Floor) 11A, MIRZA GHALIB STREET, KOLKATA-700087.

e- mail: ce-swc@wb.gov.in

Memo No. 227 /Engg/SWC/2023-2024

Dated: 03.07.2023

NOTICE INVITING TENDER No. 20 of 2023-24 of SE, WBSWC

Sealed Tenders in printed Tender Forms as specified below are invited as per particulars given below and will be received by the Superintending Engineer, WBSWC, on the date and up to the time specified therein and shall be opened soon thereafter in presence of such tenderers who may choose to be present.

1. Name of the work As per enclosed list.

As per enclosed list. 2. Name & address of the Officer concerned

As per enclosed list. 3. Contractors eligible to submit tender

As per enclosed list. 4. Estimated value of the work put to tender

As per enclosed list. Time of completion for the work

As per enclosed list. 6. Earnest money

The successful tenderers will have to Security Deposit

Keep security deposits as per rule.

W.B. Form No.2911(ii) incl. up-to date 8. Printed W. B. Tender Form in which tender Corrigenda & addenda thereof as per

is to be submitted.

Order of Govt.

As per enclosed list. 9. Price per copy of the specified W.B. Tender

10. Price per copy of the set of other tender As per enclosed list. Documents

12.07.2023 up to 2.00 P.M.

11. Last date & time limit of application forms 14.07.2023 up to 2.00 P.M.

12. Last date &time limit for permission

From this office -- West Bengal State 13. Blank tender forms may be obtained Warehousing Corporation, Khadyashree

Bhavan (1st. Floor), 11A, Mirza Ghalib Street,

Kolkata-700087.

....CONTD/2

(2)

14. Last date &time limit for submission of

Tender.

17.07.2023 up to 3.00 P.M. and the

Tender will be opened on the same day

at 4.00 P.M.

15. Place where tenders are to be submitted

Tender box kept in the office of the

Superintending Engineer, WBSWC

16. Printed Schedule of Rates applicable for the

work.

As per P.W.D (W.B) schedule of rates

W.e.f 01.12.2015 with up to date addenda & corrigenda Printed price Schedule may be obtained through

Website: www.pwdwb.in

17. With whom the acceptance of the

Tenders vest

Tender Committee, WBSWC.

Tender documents, specific price schedule of items for the works and other relevant particulars may be seen by the intending tenderers in the office of the Executive Engineer, WBSWC, on all working days between 11.00 A.M to 4.00 P.M & through website: www.warehousingwb.com.

Intending tenderers are required to produce PAN Card, Trade Licence, P. Tax Deposit Challan, P. Tax Clearance Certificate, GST registration certificate & IT return for the current year, all in original along with one set of self-attested Xerox copies to the Superintending Engineer at the time of application for being entitled to submit tender papers. It may be emphasized that WITHOUT THE ABOVE DOCUMENTS IN ORIGINAL THE APPLICATION MAY BE CANCELLED.

The contractor will have to arrange all tools and plants and construction materials required for the work.

Earnest money in the shape of Demand Draft in favour of "West Bengal State Warehousing Corporation" payable at Kolkata must be deposited along with the tender.

If the dates fall on holidays or on days of bandh or natural calamity, the dates defer to next working days. Superintending Engineer, WBSWC reserves the right to refuse any applicant without assigning any reason whatsoever and no challenge against such refusal will be entertained.

All tenderers are requested to be present personally during the opening of the tender positively. If considered necessary, instant bid may be conducted immediately after opening of the tender to lower down the rates and in no case his/their absence will stand against holding the same.

and only 123

....CONTD/3

In case of inadvertent typographical mistake found in the specific price schedule of rates, the same will be treated to be so corrected as to conform with the prevailing relevant schedule of rates and/or technically sanctioned estimate.

The intending tenderer is required to quote the rate in figures as well as in words in his own handwriting and in same ink as percentage above/below or at par than the relevant price schedule of rates. The intending tenderer is required to sign in English, Bengali or Hindi. Signature of tenderer in all location must be identical.

Conditional tender will not be entertained.

The accepting authority reserves the right to reject any or all the tenders without assigning any reason and he will not be bound to accept either the lowest tender or any of the tenders.

IN CASE OF AFTER GETTING PERMISSION FOR A PARTICULAR NIT WHO WILL NOT PARTICIPATE IN THE TENDER WITHOUT ANY VALID GROUND WOULD NOT BE ALLOWED FOR 3 (THREE) SUCCESSIVE NIT/NIQ OF THIS OFFICE.

In terms of Finance Department's order no.853-F dated 01.02.2006, communicated under circular no.599A/4N-28/06 dated 27.09.2006 of the Account Branch, Public Works Department, Government of West Bengal, a cess of 1% of the cost of construction works etc. will be levied from the bills of all the works and the amount so collected will be remitted subsequently to the "West Bengal Building & other construction workers Welfare Board" such levying of cess @1% for the same purpose will be effective from 01.11.2006 and GST will be deducted as per latest rule.

Superintending Engineer
WEST BENGAL STATE WAREHOUSING CORPORATION

Dated: 03.07.2023

Memo No. 227 /Engg/SWC/2023-24/1(4),

Copy forwarded for information and wide circulation through Notice Board to:

1. The Managing Director, WBSWC.

- 2. The Deputy Secretary(Advertisement), F&S Dept. For information & wide circulation.
- 3. The Chief Engineer, WBSWC.
- 4. The Deputy Director, Food, WBSWC.
- 5. This Office NOTICE BOARD.

Superintending Engineer

WEST BENGAL STATE WAREHOUSING CORPORATION

....CONTD/4

Annexure of NIT No. 20 of 2023-24 of SE,WBSWC Name of work: Repairing of Foundation wall of Weighbridge at Memari RIDF in the district of Purba Bardhaman.

SI. No.	ITEMS OF WORK	Estimated amount put to tender (Rs)	Earnest money (Rs) to be deposited with tender	Price of Formal Tender paper for L1 Bidder (Rs)	Time of completion	Rate to be quoted in % both in Fig. and words
1	As per BOQ	55,723/- (Rupees Fify Five Thousand Seven Hundred Twenty Three only)	1,115/- (Rupees One Thousand One Hundred Fifteen only)	255/- x 2 = 510/- In the form of Bank Draft	60 days	

Superintending Engineer
WEST BENGAL STATE WAREHOUSING CORPORATION

Percentage BOQ

Tender Inviting Authority: West Bengal Sate Warehousing Corporation. Name of Work: Repairing of Foundation wall of Weighbridge at Memari RIDF in the district of Purba

Dismantling all types of plain cement concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m amaterials at site and removing rubbish as directed within a lead of 75 m amaterials at site and removing rubbish as directed within a lead of 75 m amaterials at site and removing rubbish as directed within a lead of 75 m amaterial site of the site of th	_	NIT No: 20 OF 2023-24 OF SUPERVISION				ui p	۳			
Dismantling all types of plain cement concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m and materials at site and removing rubbish as directed within a lead of 75 m and materials at site and removing rubbish as directed within a lead of 75 m and materials at site and removing rubbish as directed within a lead of 75 m as directed in the time including removing. Spreading or stacking the spoils soll but excluding laterite or sandstone; including removing, spreading or stacking the spoils levelling, dissing and framming the bottom, bailing out water as required complete (a) depth of Earth work in filling in foundation itenches or plinith with good earth, in layers not exceeding 150 mm including watering and ramming etc. layer by layer complete exceeding 150 mm including watering and ramming the super by layer complete exceeding 150 mm including watering and ramming the layer by layer complete exceeding 150 mm including watering and ramming the spoils exceeding 150 mm including watering and ramming the spoil exceeding 150 mm including watering and ramming the spoil exceeding 150 mm including watering and ramming the spoil exceeding 150 mm including watering and ramming the spoil exceeding 150 mm including watering and ramming the spoil exceeding 150 mm including watering and print provides and provided to proper level and filling joints with powdered earth or local sand. Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below filooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement, and, in ground filoor as per relevant IS codes. a) Pakur Variety Column Footing Tie beam Plinth Protection Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved is thickness with required bracing for concrete slab	NIT No: 20 OF 2023-24 OF SUPERINTENDING ENGINEER, WBSWC									
In ground floor including roof a) upto 150 mm thick For Tie Beam Farth work in excavation of foundation trenches or drains, in all sorts of soil (including mixed within a lead of 75 m as directed. The item includes necessary trimming the solds of trenches soil but excluding laterite or sandstone including removing. speading or stacking the spoils levelling, dressing and ramming the bottom, bailing out water as required complete (a) depth of several and or 150 mm including watering and ramming let layer by layer complete (a) depth of exceeding 150 mm including watering and ramming etc. layer by layer complete (Payment to be made on the basis of measurement of finished quantity of work) (a) With earth obtained from excavation of foundation 273 of Excavation Single brick flat soling of picked jhama bricks including ramming and dressing bed to proper level and filling joints with powdered earth or local sand. Sqm Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below flooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal excluding shuttering and reinforcement, if any, in ground floor as per relevant 15 codes. a) Pakur Variety Column Footing Tie beam Pinth Protection Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant 15 codes. a) Pakur Variety Column footing Tie beam Column Column Column Column Column Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant 15 codes. a) Pakur Variety Column footing Tie beam Column footing Tie beam Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness w	_	Description of Item		Qty	Rate Including 18% GST& 1% CESS	Ame	ount			
Earth work in excavation of foundation trenches or drains, in all sorts of soil (including mixed soil but excluding laterite or sandstone) including removing, spreading or stacking the spoils levelling, dressing and ramming the bottom, bailing out water as required complete (a) depth of Earth work in filling in foundation trenches or plinth with good earth, in layers not exceed a 1500 mm. Earth work in filling in foundation trenches or plinth with good earth, in layers not exceed with 1500 mm. Earth work in filling in foundation trenches or plinth with good earth, in layers not exceed with 1500 mm. Earth work in filling in foundation trenches or plinth with good earth, in layers not exceed with 1500 mm. Earth work in filling in foundation trenches or plinth with good earth, in layers not exceed with 1500 mm. Earth work in filling in foundation or filling in ground in the exceeding 1500 mm. Earth work in filling in foundation or filling in ground for size in foundation. 273 of Excavation Single brick flat soling of picked jhama bricks including ramming and dressing bed to proper level and filling joints with powdered earth or local sand. Sqm Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below flooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. a) Pakur Variety Column Footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved 8 thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) 1) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation	00	eypes of plain cement concrete works, stacking serviceable and removing rubbish as directed within a lead of 75 m including roof.a) upto 150 mm. thick	n	2 00	1119 10	2,	235 00			
Earth work in filling in foundation trenches or plinth with good earth. in layers not exceeding 150 mm including watering and ramming etc. layer by layer complete (Payment to be made on the basis of measurement of finished quantity of work) (a) With earth obtained from excavation of foundation 2/3 of Excavation Single brick flat soling of picked jhama bricks including ramming and dressing bed to proper level and filling joints with powdered earth or local sand. Sqm Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below flooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. a) Pakur Variety Column Footing Tie beam Plinth Protection Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved study props and thick hard wood planks of approved thickness with required bracing for concrete slasbs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) 1) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-in-Charge For PCC and RCC (a) Foundation and Plinth Columns Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	n n	vation of foundation trenches or drains, in all sorts of soil (including mixed aterite or sandstone) including removing, spreading or stacking the spoils may as directed. The item includes necessary trimming the sides of trenches, with the bottom of the sides of trenches.	3	4.15	14214.60		590.00			
2/3 of Excavation Single brick flat soling of picked jhama bricks including ramming and dressing bed to proper level and filling joints with powdered earth or local sand. Sqm Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below flooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. a) Pakur Variety Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation and Plinth Columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	fil	g in foundation trenches or plinth with good earth, in layers not					-			
2/3 of Excavation Single brick flat soling of picked jhama bricks including ramming and dressing bed to proper level and filling joints with powdered earth or local sand. Sqm Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below flooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. a) Pakur Variety Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation and Plinth Columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	c	ained from excavation of foundation	+							
Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below flooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per Plinth Protection Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	tic	%m	13	2.77	9241.22		256.00			
or below flooring or roof terracing or in foundation or in foundation trenches. Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. Oldinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge. For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	il.	soling of picked jhama bricks including ramming and dressing vel and filling joints with powdered earth or local sand.	m	4.63	386.14		1,786.00			
size) excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. a) Pakur Variety Column Footing Tie beam Plinth Protection Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge. For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary) cutting to requisite length, hooking and bending to correct shape, placing in proper position and	וכ	g or roof terracing or in foundation or in foundation trenches.	m	7.00	28.60		200.00			
Tie beam Plinth Protection Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. A) Pakur Variety Column footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved intickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation and Plinth Columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and) (huttering and reinforcement, if any, in ground floor as per m	13	0.70	5756.22		4,047.00			
Plinth Protection Ordinary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	it									
nominal size) excluding shuttering and reinforcement if any, in ground floor as per relevant IS codes. a) Pakur Variety Column footing Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	or									
Tie beam Column Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge. For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and)	xcluding shuttering and reinforcement if any, in ground	13	1.41	6359.38		8,983.00			
Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	_									
Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge. For PCC and RCC (a) Foundation and Plinth Column footing columns Tile beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and										
upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge. For PCC and RCC (a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods,initial straightening and removal of loose rust (if necessary)cutting to requisite length,hooking and bending to correct shape, placing in proper position and	_									
f) 25 mm to 30 mm thick shuttering without staging in foundation as per decision & direction of Engineer-In-Charge. For PCC and RCC (a) Foundation and Plinth Column footing columns Tile beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary)cutting to requisite length, hooking and bending to correct shape, placing in proper position and	h ai	approved stout props and thick hard wood planks of approved equired bracing for concrete slabs, beams and columns, lintels at including fitting, fixing and striking out after completion of	15.15 M2		5 244.32		3,701.0			
(a) Foundation and Plinth Column footing columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods, initial straightening and removal of loose rust (if necessary) cutting to requisite length, hooking and bending to correct shape, placing in proper position and	i i	n thick shuttering without staging in foundation as per decision & er-in-Charge. For PCC and RCC					-			
Columns Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods,initial straightening and removal of loose rust (if necessary)cutting to requisite length,hooking and bending to correct shape ,placing in proper position and						-	-			
Tie beam Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods,initial straightening and removal of loose rust (if necessary)cutting to requisite length,hooking and bending to correct shape ,placing in proper position and	n					-+				
Plinth Protection Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods,initial straightening and removal of loose rust (if necessary)cutting to requisite length,hooking and bending to correct shape ,placing in proper position and										
Reinforcement for reinforced concrete work in the all sorts of structures including distribution bars stirrups, binders etc. including supply of rods,initial straightening and removal of loose rust (if necessary)cutting to requisite length,hooking and bending to correct shape ,placing in proper position and										
including distribution bars stirrups, binders etc. including supply of rods,initial straightening and removal of loose rust (if necessary)cutting to requisite length,hooking and bending to correct shape ,placing in proper position and	ıC									
per drawing and direction	a g	tion bars stirrups, binders etc. including supply of rods,initial removal of loose rust (if necessary)cutting to requisite and bending to correct shape ,placing in proper position and suge black annealed wire at every intersection, complete as	MT 0.		3 66005.06		8,78			
(i) Tor steel/Mild steel (a) For works in foundation, basement and upto roof of ground floor / upto 4m.	-									

	1.2% of the volume of concrete.				
	Total Volume of Concrete = 1.41 M3				
10	Neat cement punning about 1.5mm thick in wall, dado, window sill, floor etc. NOTE:Cement 0.152 cu.m per100 sq.m.	Sqm	28.50	40.52	1,155.00
11	Brick work with 1st class bricks in cement mortar (1:4) (b) In superstructure, ground floor	Cum	1.86	6321.31	11,754.00
12	Plaster (to wall, floor, ceiling etc.) with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints including throating, nosing and drip course, scaffolding/staging where necessary (Ground floor). [Excluding cost of chipping over concrete surface] (i) With 1:6 cement mortarc) 15 mm thick plaster (Exterior)	Sqm	28.50	162.08	4,619.00
13	Applying Exterior grade Acrylic primer of approved quality and brand on plastered or cencrete surface old or new surface to receive decorative textured (matt finish) or smooth finish acrylic exterior emulsion paint including scraping and preparing the surface throughly, complete as per manufacturer's specification and as per direction of the EIC.In Ground Floor:(b) Two Coats	M2	57.00	53.75	3,064.00
	on both new and existing wall				
18	Protective and Decorative Acrylic exterior emulsion paint of approved quality, as per manufacturer's specification and as per direction of Engineer-in-Charge to be applied over acrylic primer as required. The rate includes cost of material, labour, scaffolding and all ncidental charges bu excluding the cost of primer. In Ground floor(Two Coat)a) Normal Acrylic Emulsion.	M2	57.00	79.85	4,551.00
				Ť	otal 55,723.0
	Quoted Rate in Figures				
	Quoted Rate in Words				

Superintending Engineer

WEST BENGAL STATE WAREHOUSING CORPORATION